



OFFICIAL LISTING

NSF International Certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI Standard 60 - Drinking Water Treatment Chemicals - Health Effects

This is the Official Listing recorded on May 1, 2012.

Enviro Tech Chemical Service Inc
500 Winmoore Way
Modesto, CA 95358
209-581-9576

Facility: Modesto, CA

Chemical/ Trade Designation	Function	Max Use
Miscellaneous Water Supply Products		
BioSide™ HS 15% ^{[2] [3] [4]}	Membrane Cleaner	NA
BioSide™ HS 15% ^[1]	Membrane Cleaner	30 mg/L
	Reverse Osmosis Antiscalant	
BioSide™ HS 5% ^{[2] [3] [4]}	Membrane Cleaner	NA
BioSide™ HS 5% ^[1]	Membrane Cleaner	90 mg/L
	Reverse Osmosis Antiscalant	
BSL 8000 ^[5]	Other	NA
BSL Pro ^[5]	Other	NA
PERASAN™ ^[1]	Membrane Cleaner	30 mg/L
	Reverse Osmosis Antiscalant	
PERASAN™ ^{[2] [3] [4]}	Membrane Cleaner	NA
PERASAN™ 'A' ^{[2] [3] [4]}	Membrane Cleaner	NA
PERASAN™ 'A' ^[1]	Membrane Cleaner	90 mg/L
	Reverse Osmosis Antiscalant	
REFLEX™ ^{[2] [3] [4]}	Membrane Cleaner	NA

- [1] This product is designed to be used upstream of a carbon absorption system. Use of this product shall be followed by chlorination to remove trace levels of hydrogen peroxide.
- [2] These products are designed to be used off-line and flushed out prior to using the system for drinking water, following manufacturer's use instructions.
- [3] The pH of the influent and effluent water should be monitored to ensure that all traces of the product have been removed before placing into service.
- [4] Drain and flush system until the hydrogen peroxide and peracetic acid concentrations fall below 1 ppm.
- [5] These products are used offline to remove deposits from water tank surfaces. BSL 8000 and BSL Pro are used in a 10:1 ratio at a rate of 60 mg/L. The tank is rinsed to remove any residual product before returning to service.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.